



CERTIFICATE OF COMPLIANCE

Certificate Number: SGSNA/23/SZ/00465

Contract Number: 801593

Certificate Project Number: SZ-CERT231203769

Certified Product: Power station inverter (product name: EcoFlow DELTA Pro Ultra Inverter)

Trademarks: ECOFLOW; EF ECOFLOW

Model(s): EFYJ751-PCS-US

Technical Data: See page 2

Certificate Holder: EcoFlow Inc.
1st Floor, Building 1, Plant E, Jiehe Industrial City, Shuitian Community, Shiyan Street, Bao'an District, Shenzhen, Guangdong, China

This certificate supercedes previous certificates issued with the same certificate number. Certification is valid when products are indicated on the SGS directory of certified products at www.sgs.com or using the QR code below. The product is certified according to ISO/IEC Guide 17067, Conformity assessment - Fundamentals of product certification, System 3, and in accordance with:

UL 1012, 8th Ed., Rev. March 30, 2021

UL 1778, Fifth Edition, revised April 28, 2023

CSA C22.2 No. 107.3-14, Third Edition

Authorized by:

Effective date: 20 December 2023



Jason Wei
Certifier



Certification Body

Connectivity & Products, a division of SGS North America Inc.
620 Old Peachtree Road, Ste. 100, Suwanee, GA 30024, USA
t +1 770 570 1800 f +1 770 277 1240 www.sgs.com



CERTIFICATE OF COMPLIANCE

Certificate Number: SGSNA/23/SZ/00465

Contract Number: 801593

Certificate Project Number: SZ-CERT231203769

Technical Data:

AC Input (charge only): 100-120 V~, 15 A max. (duration time <3hrs when current exceeds 12A), 200-240 V~, 12.5A max., 50/60Hz;

AC Input (Bypass mode): 100-120 V~, 15 A max., 50/60Hz (duration time <3hrs when current exceeds 12A);

(5+8) Power Input/Output: 100-120 / 200-240 V~, 30A max., 50/60Hz;

High-PV Port input:

Max. Input Voltage 450 Vd.c.; MPPT Voltage range 80-400 Vd.c.; Max. input current 15 A; Isc PV 23A max.;

Low-PV Port input:

Max. Input Voltage 150 Vd.c.; MPPT Voltage range 30-130 Vd.c.; Max. input current 15 A; Isc PV 23A max.;

Battery charge input 80-116.8 Vd.c., 60A max.;

Battery discharge output 80-116.8 Vd.c., 107A max.;

Total max. output power 7802 W;

DC output port 12.6 Vd.c., 30A max.;

AC output (discharge only): 120/240 V~, 60Hz, 7200W total, 30A(x2) max. per port, 20A(x4) max. per port;

AC output (bypass mode): 100-120 V~, 50/60Hz, 3600W max. total, 30A(x2) max. per port, 20A(x4) max. per port;

USB-A output (x2): 5Vd.c., 2.4A max. (total 24W);

USB-C output (x2): 5/9/12/15/20 Vd.c., 5A max. (total 200W)

Certification Body

Connectivity & Products, a division of SGS North America Inc.
620 Old Peachtree Road, Ste. 100, Suwanee, GA 30024, USA
t +1 770 570 1800 f +1 770 277 1240 www.sgs.com