

EcoFlow OCEAN Pro Battery

Complete Product Datasheets

Product	Product Name	EcoFlow OCEAN Pro Battery
	Model Number	EF-BP-10
Battery Technical Specifications (per unit)	Battery Cell Type	Lithium Iron Phosphate (LFP)
	Nominal Battery Energy	10kWh
	Rated Voltage	400V DC
	Voltage Range	380 - 550V DC
	Maximum Continuous Input / Output Current	Total 63A (26.32A maximum per units)
	Maximum Continuous Discharge Power	10kW
	Maximum Continuous Charge Power	5kW
	Energy Scalability	Up to 8 battery units supported by one OCEAN Pro Inverter
Compliance Information		System: UL9540
	Safety	BP: UL 1973, UN 38.3, ISTA-3A
		FCC Part 15B
	Emissions	ICES-003
		California Proposition 65
	Environmental	TSCA
	Seismic	AC156, IEEE 693-2005 (high)
	Fire Testing	UL 9540A, UL9540B
Environmental Specifications	On a serial seri	-4°F to 140°F (-20°C to 60°C)
	Operating Temperature	>113°F (45°C) Derating
	Operating Humidity (RH)	Up to 100%, condensing
	G. T. I	-4°F to 86°F (-20°C to 30°C), up to 95% RH,
	Storage Temperature	noncondensing, State of Energy (SOE): 25% initial
	Maximum Elevation	9843ft (3000m)
	Environment	Indoor and outdoor rated
	Enclosure Rating	NEMA 3R
	Ingress Protection (IP) Rating	IP67 (Battery & Power Electronics), IP55 (Battery Wiring Compartment)
	Pollution Rating	PD3
	Operating Noise@1m	< 45 db(A) typical , < 60 db(A) maximum
	Mounting Options	Floor or wall mount
	Height/inches	45.3in/1150mm
Mechanical Specifications	Width/inches	45.3ii/130iiiiii 17.3in/439mm
	Depth/inches	10.8in/274mm
	Weight/lbs	245.8lbs/111.5kg (Top cover not included 3.7kg/8.15lbs)
	A A EIRI II A III A	240.0109/111.0kg (Top Cover Flot Il Cluded 3.7kg/0.10108)