


Solar Battery Solution for Houses

EcoFlow PowerOcean Single-Phase

Safety and Power Independence in Every Charge





Reliable Power Independence. Made Tangible.

Up to 6kW Output Backup Power

The EcoFlow PowerOcean equips you with up to 6kW of continuous off-grid power. Independence isn't just about energy; it's about continuity during power outages, getting all essential home appliances backed up at once, and ensuring an uninterrupted lifestyle. Feel the power of independence.

Up to 12kW PV Input

Capture more solar energy from your rooftop—powering your home and charging your battery faster, all-in-one system.



Uncompromising Safety. Steady Performance.

90V MPPT Charger Controller

Experience uncompromised efficiency across all weather conditions. With PowerOcean's built-in 90V MPPT charge controller, you can expect superior performance, day in and day out.

AFCI Protection

AFCI protects the branch circuit wiring from dangerous arcing faults that could initiate an electrical fire.

First SA TS 5398:2025

Certification Issued by CCS. Safety is a necessity, not an option.



PowerOcean Battery Pack

LFP Performance. Beautifully Powered.

5kWh/8kWh

Up to 40kWh per system

Up to 10,000

Cell Cycling

6.4 kW

Maximum Discharging Power

8.2 kW

Peak Discharge Power(10 Seconds)

15 Years*

Official Warranty

* 10-Year compulsory warranty and a 5-year optional extended warranty for the OCEAN 2 8kWh LFP Battery.




All-Round Safety, Long-Term Peace of Mind

6 Layers Passive Protection

- Aerogel thermal insulation
- FPC short-circuit protection
- Thermal and fire-resistant insulation
- Built-in fire prevention module
- Explosion-proof pressure relief valve
- Full die-cast aluminum alloy enclosure

4 Layers Active Protection

- NTC temperature monitoring
- AFE chip built into the BMS
- Multi-MOS Active Balancing
- Cloud-based BMS early warning system





Effortlessly Scalable. Unquestionably PowerOcean.

Start Small. Kickstart from 1 Battery.


Built-in DC-DC converter in each battery pack allows our single-phase hybrid inverter to operate with even one pack simply.


Your Energy Needs. Your Call.

Start with a single 5kWh battery pack, up to 40 kWh per system, and watch your power solution expand alongside your needs.

Old Batteries. New Life.

Mix & match your old and new batteries freely. Unleash the full capacity of all packs with isolated battery management, 0 impact from short-board limitation.





Battery Switch

IP65-Certified for Ultimate Protection

EcoFlow PowerOcean features an IP65 certification, ensuring it stands strong against dust ingress and is resistant to low-pressure water jets from any direction.


Installation Option Ready for Easy Outdoor Installation

Embrace the outdoors with confidence, PowerOcean is designed to meet the critical requirements of the newly established PAS 63100:2024 standards, ensuring the highest safety performance level. This compliance makes PowerOcean ideal for outdoor installations, giving you placement options without compromising safety or efficiency.



Open Ecosystem. Total Home Energy Control.

The EcoFlow Home Energy Ecosystem connects solar, battery storage, EV charging, and other smart home devices into one seamless platform, giving homeowners complete visibility and control over how energy is generated, stored, and used. EcoFlow works with a variety of smart home platforms and protocols to deliver the ultimate seamless smart home energy experience.



Accessories


EcoFlow Gateway (Single-Phase)

EcoFlow Gateway supports 63A for true whole-home backup, connects directly to your main panel for faster installation, and accepts multiple energy inputs for flexible, reliable power.



EcoFlow PowerInsight 2 Monitor

11-inch HD display tracks power flow and unifies smart home control. Matter 1.4 compatible with Google Nest & major brands for effortless connected living.




EcoFlow App and Web Portal

EcoFlow App and Web Portal for End-Users

- Intuitive power flow monitoring
- Say goodbye to high energy bills with Self-Powered Mode
- Viewing power generation and consumption data through an application
- Customise the system's working mode and parameters



Scan QR code to download




EcoFlow Pro App and Web Portal for Installers

- Ultra-fast 3-step commissioning process
- Comprehensive map view of authorised systems
- Comprehensive and detailed data to assist you in system fault analysis



Scan QR code to download



*All specifications and descriptions shown may differ from the actual specification of the product. EcoFlow reserves the right to make changes and amendments to the product shown and described here at any time without prior notice of such change. All functionality, features, specifications, design and other product information displayed in this webpage including, but not limited to, components, performance, availability, and capabilities of the product are subject to change without notice. The contents and simulated images within the screen are for demonstration purposes only.

EcoFlow PowerOcean Single-Phase Hybrid Inverter

Technical parameters		EF HD-P1-3K-S1-A	EF HD-P1-5K-S1-A	EF HD-P1-6K-S1-A
DC Input (PV)	Maximum PV Power (kW)	9	11	12
	Maximum Input Voltage (V)	600		
	Mppt Voltage Range (V)	90V-520		
	Maximum Input Current per MPPT (A)	18 (single PV input), 16 (dual PV input)		
	Maximum Short Circuit Current per MPPT (A)	20		
	Backfeed Current to the PV Array (A)	0		
	Number of MPPTs	2		
	Overvoltage Category	II		
DC Input (Battery)	Rated Voltage (V)	790		
	Maximum Voltage (V)	800		
	Rated Current (A)	7.6		
	Maximum Current (A)	7.6	7.6	8.4
	Maximum Battery Capacity (kWh)	20.4		
AC Input	Grid Connection	L+N+PE		
	Overvoltage Category	III		
	Rated Input Power (W)	3000	5000	6000
	Maximum Apparent Power (VA)	3000	5000	6000
	Rated Input Voltage (V)	220/230/240, L+N+PE		
	Maximum Input Current (A)	16	26.7	32
	Nominal Frequency (Hz)	50/60		
AC Output (On-grid)	Grid Connection	L+N+PE		
	Overvoltage Category	III		
	Rated Output Power (W)	3000	5000	6000
	Maximum Apparent Power (VA)	3000	5000	6000
	Rated Output Voltage (V)	220/230/240, L+N+PE		
	Rated Output Current (A)	13.1	21.7	26.1
	Maximum Output Current (A)	15	25	30
	Nominal Frequency (Hz)	50/60		
	Total Harmonic Distortion (At Rated Power)	≤5%	≤3%	≤3%
	Power Factor	0.8 leading ~ 0.8 lagging		
AC Output (Backup load)	Maximum Output Power (VA)	3000	5000	6000
	Nominal Output Voltage (V)	220/230/240, L+N+PE		
	Nominal Frequency (Hz)	50/60		
	Maximum Output Current (A)	16	26.7	32
	Rated Output Current (A)	13.1	21.7	26.1

Technical parameters		EF HD-P1-3K-S1-A	EF HD-P1-5K-S1-A	EF HD-P1-6K-S1-A
Efficiency	Maximum Efficiency	>96%	>96.5%	>96.5%
	European Weighted Efficiency	>95%	>96%	>96%
Protection	GECI	Integrated		
	AFCI	Integrated		
	Insulation Resistance Detection	Integrated		
	PV Reverse Polarity Protection	Integrated		
	AC Overcurrent Protection	Integrated		
	AC Short-Circuit Protection	Integrated		
	AC Overvoltage Protection	Integrated		
	Anti-islanding Protection	Integrated		
	Protective Class	I		
Compliance	Certificates	RCM MARK		
	Safety Standard	IEC/EN62109-1, IEC/EN62109-2		
	Grid-Tied Standards	G98, G99, G100, VDE-AR-N 4105, CEI 0-21, UTE C15-712-1, VDE0126-1-1, EN 50549-1, C10/11, NTS631, UNE 217001, UNE 217002, PPDS, PTPIREE, PSE, NC RfG, ORDINANCE No.140, NRS 097-2-1, AS/NZS 4777.2		
	EMC	EN/IEC 61000-6-1/2/3/4, IEC 61000-4-16/18/29, IEC 61000-2-2, EN 300328, EN 301489-1, EN 301489-17, EN IEC 62311		
General	Cascading	Up to 60kWh battery capacity*1		
	Topology	Non-isolated		
	Ingress Protection Rating	IP65		
	Operating Temperature Range (°C)	-20 to 50 (derating when the temperature is above 40 or below 0)		
	Storage Temperature Range (°C)	-30 to 60		
	Operating Humidity	0%-100% (Condensing)		
	Maximum Operating Altitude (m)	3000 (derating above 2000)		
	Weight (kg)	21.5		
	Dimensions (WxDxH)(mm)	679.6x182.7x280 (without IOT & Wi-Fi module)		
	Noise Emission (dB)	40*2		
	Self-Consumption at Night (W)	<30		
	Cooling Method	Natural convection		
	Communication Method	RS485 & CAN & Wi-Fi & Bluetooth & WAN & 4G		
	Wi-Fi Frequency Range, Maximum Output Power	2400 MHz-2483.5 MHz, 17 dBm		
	Bluetooth Frequency Range, Maximum Output Power	2400 MHz-2483.5 MHz, 8 dBm		
	Pollution Degree	PD3		
	Environmental Category	Outdoor/Indoor		
	Country of Manufacture	China		

*1 For a total battery capacity of 60kWh, 3 hybrid inverters are required. One hybrid inverter can support a maximum of 20kWh.

*2 Noise emission value measured under laboratory conditions: ambient temperature 25°C, free-field acoustic environment, measurement position 1m directly in front of the equipment. Actual noise levels may vary depending on load conditions, installation methods and environmental reflection characteristics. This data is only applicable to the declared test conditions.

Please be advised that EcoFlow reserves the right to modify the design, components, and specifications of its products at any time without prior notice or obligation. The actual product details may vary from those shown or described in this brochure.

EcoFlow PowerOcean LFP Battery

Number of Battery Packs		EF BD-5.1-S1 EF BD-B-S1	EF BD-10.2-S1 EF BD-B-S1	EF BD-15.3-S1 EF BD-B-S1	EF BD-20.4-S1 EF BD-B-S1
Performance	Battery Nominal Capacity	5.1	10.2	15.3	20.4
	Battery Usable Capacity(kWh)*1 (95% Depth of Discharge)	4.8	9.7	14.5	19.4
	Max. Discharge Power (W)	3300	6600	9900	13200
	Max. Charge Power (W)	2500	5000	7500	10000
	Nominal Voltage(V)	800			
	Operating Voltage Range(V)	720-960			
	Battery Short Circuit current (A)	200A for 300 us	400A for 300 us	600A for 300 us	800A for 300 us
	Battery Maximum Discharge Current (A)	4.4	8.8	13.2	17.6
	Battery Maximum Charge Current (A)	3.3	6.6	9.9	13.2
	Rated DC Power (kW)	Discharge: 3.3 Charge: 2.5	Discharge: 6.6 Charge: 5.0	Discharge: 9.9 Charge: 7.5	Discharge: 13.2 Charge: 10
	BatteryCell Type	LiFePO ₄			
Performance	Certicates	RCM MARK			
	Safety Standard	IEC 62619, IEC 62040-1, IEC 62477-1, ISO13849			
	Delivery Standard	UN38.3			
	EMC	IEC 61000-6-1/3			
General	Dimension (mm)	680x183x424(±1)	680x183x848 (±1)	680x183x1272(+1)	680x183x1696(+1)
	Weight (kg)	55.5	111	166.5	222
	Installation	Floor Stand: A stack of up to 4 batteries Wall Mounted: A stack of up to 3 batteries			
	Operating Temperature (°C)	-20 to 50			
	Max. Operating Altitude (m)	3000			
	Communication Method	CAN			
	Cooling Method	Natural Convection			
	Noise Emission (dB)	≤35*2			
	Relative Humidity	0%-100% (Condensing)			
	Active Aerosol Fire Prevention Module	Integrated			
	Protection Level	IP65			
	Protective Class	I			

*1 To maintain optimal battery performance in low-temperature environments, the depth of discharge (DoD) may vary with actual temperature. This is a normal fluctuation.

*2 Noise emission value measured under laboratory conditions: ambient temperature 25°C, free-field acoustic environment, measurement position 1m directly in front of the equipment.Actual noise levels may vary depending on load conditions, installation methods and environmental reflection characteristics. This data is only applicable to the declared test conditions.

EcoFlow OCEAN 2 LFP Battery

Technical parameters		EF OCEAN 2 LFP Battery 8kWh EF BD-8-S2A	EF OCEAN 2 LFP Battery 5kWh EF BD-5-S2
Performance	Battery Nominal Capacity(kWh)	8.03	5.02
	Battery Usable Capacity¹(kWh)	8.03	5.02
	Battery Cell Type	LiFePO₄	LiFePO₄
	Nominal Charging Power(kW)	4.1	2.5
	Nominal Discharging Power(kW)	4.1	3.4
	Maximum Discharging Power²(kW)	6.4	4.08
	Nominal Voltage(V)	400 / 800	400 / 800
	Operating Voltage Range(V)	360-520 / 720-960	360-520 / 720-960
General	Dimension(WxDxH)(mm)	680 x 196 x 378	680 x 196 x 279
	Weight(kg)	67.5	46
	Installation	Floor Stand: A stack of up to 4 batteries Wall Mounted: A stack of up to 3 batteries	Floor Stand: A stack of up to 4 batteries Wall Mounted: A stack of up to 3 batteries
	Operating Temperature³(°C)	-20~ 55	-20~ 55
	Storage Temperature(°C)	-25~ 60	-25~ 60
	Max. Operating Altitude⁴(m)	3000	3000
	Relative Humidity	0% ~100%	0% ~100%
	Cooling Method	Intelligent Air Cooling	Natural Cooling
	Ingress Protection Rating	IP66	IP66
	Anti-theft	Supported	Supported
	Battery Heating	Supported	Supported
	Communication method	CAN	CAN
	Country of Manufacture	China	China
	Protection	Over-charge/over-discharge protection, over-voltage/under-voltage protection, over-current protection, short-circuit protection, reverse-polarity protection, temperature protection, thermal-runaway protection, leakage-current protection, insulation protection, over-pressure protection, automatic power-off protection, emergency shutdown,Water Ingress Detection	Over-charge/over-discharge protection, over-voltage/under-voltage protection, over-current protection, short-circuit protection, reverse-polarity protection, temperature protection, thermal-runaway protection, leakage-current protection, insulation protection, over-pressure protection, automatic power-off protection, emergency shutdown
Compliance		IEC/EN 62619, IEC/EN 62040-1, IEC/EN 62477-1, ISO 13849-1, EN IEC 61000-6-1, EN IEC 61000-6-2, EN IEC 61000-6-3, EN IEC 61000-6-4, UN 38.3, SA TS 5398	IEC/EN 62619, IEC/EN 62040-1, IEC/EN 62477-1, ISO 13849-1, EN IEC 61000-6-1, EN IEC 61000-6-2, EN IEC 61000-6-3, EN IEC 61000-6-4, UN 38.3
1. Test conditions: 100% depth of discharge, 0.2C rate charge & discharge on average of 25°C, at the beginning of life. 2. In a laboratory environment at 25°C ambient and device temperature with PowerOcean Hybrid Inverter, the discharge time at this power is no more than 30 minutes for Ocean 2 LFP 8kWh and 20 minutes for Ocean 2 LFP 5kWh. Under different usage conditions, actual performance may vary. 3. Power may be derated when the temperature exceeds 40°C. 4. Power may be derated above 2000 m.			

Contact EcoFlow



Website



LinkedIn
@EcoFlow Australia



Facebook
@EcoFlow



Facebook
Community

Website: <https://energy.ecoflow.com/au>
Email: solutionsales.au@ecoflow.com

*Information might be subject to change without notice during product improvement.